

Dimensioni e pesi elemento Gambetta spessore 10 cm					Dimensioni e pesi elemento Gambetta spessore 15 cm			
H TEGOLO (cm)	Larghezza max cm	Larghezza Min. cm	peso kg/m <sup>2</sup>	Peso max kg/m	Larghezza max cm	Larghezza Min. cm	peso kg/m <sup>2</sup>	Peso max kg/m
30	250	160	184	461	250	165	209	524
40	250	161	209	523	250	166	244	611
50	250	162	236	589	250	167	281	702
60	250	163	264	659	250	168	319	797
70	250	164	293	733	250	169	358	896
80	250	165	324	811	250	170	399	999
90	250	166	357	893	250	171	442	1106

Tabella delle lunghezze indicative dei tegoli per tipologia di utilizzo (esprese in m)

H TEGOLO (cm)	Copertura				Soppalco							
	R60		R120		R60				R120			
	Sov. 1,60	Sov. 2,20	Sov. 1,60	Sov. 2,20	Sov. 2,50	Sov. 5,00	Sov. 8,00	Sov. 10,00	Sov. 2,50	Sov. 5,00	Sov. 8,00	Sov. 10,00
	Gambetta 10 cm		Gambetta 15 cm		Gambetta 10 cm				Gambetta 15 cm			
30	6,0 ÷ 10,0	6,0 ÷ 9,0	6,0 ÷ 9,0	6,0 ÷ 8,0	5,0 ÷ 8,5	5,0 ÷ 7,5	4,0 ÷ 6,5	4,0 ÷ 5,0	5,0 ÷ 8,0	5,0 ÷ 7,5	4,0 ÷ 6,5	4,0 ÷ 5,0
40	7,0 ÷ 12,0	7,0 ÷ 11,0	7,0 ÷ 11,0	7,0 ÷ 10,0	5,0 ÷ 11,0	5,0 ÷ 9,0	5,0 ÷ 8,0	5,0 ÷ 7,5	5,0 ÷ 10,0	5,0 ÷ 8,5	5,0 ÷ 7,5	4,0 ÷ 5,5
50	8,0 ÷ 15,0	8,0 ÷ 13,5	8,0 ÷ 13,5	8,0 ÷ 12,0	6,0 ÷ 13,0	6,0 ÷ 11,5	6,0 ÷ 9,5	6,0 ÷ 9,0	6,0 ÷ 12,5	6,0 ÷ 11,0	6,0 ÷ 9,0	6,0 ÷ 8,5
60	9,0 ÷ 17,0	9,0 ÷ 16,0	9,0 ÷ 16,0	9,0 ÷ 15,0	7,0 ÷ 16,0	7,0 ÷ 13,5	7,0 ÷ 12,0	7,0 ÷ 11,0	7,0 ÷ 15,5	7,0 ÷ 13,0	7,0 ÷ 11,5	7,0 ÷ 10,5
70	9,0 ÷ 18,0	9,0 ÷ 17,0	9,0 ÷ 17,0	9,0 ÷ 16,0	8,0 ÷ 17,5	8,0 ÷ 15,5	8,0 ÷ 13,5	8,0 ÷ 12,5	8,0 ÷ 17,0	8,0 ÷ 15,0	8,0 ÷ 13,0	8,0 ÷ 12,0
80	9,0 ÷ 20,0	9,0 ÷ 19,0	9,0 ÷ 20,0	9,0 ÷ 19,0	9,0 ÷ 19,5	9,0 ÷ 17,5	9,0 ÷ 15,0	9,0 ÷ 14,0	9,0 ÷ 19,0	9,0 ÷ 17,0	9,0 ÷ 14,5	9,0 ÷ 13,5
90	10,0 ÷ 21,0	10,0 ÷ 20,0	10,0 ÷ 21,0	10,0 ÷ 20,0	10,0 ÷ 21,0	10,0 ÷ 19,5	10,0 ÷ 16,5	10,0 ÷ 15,5	10,0 ÷ 20,5	10,0 ÷ 19,0	10,0 ÷ 16,5	10,0 ÷ 15,5

Il sovraccarico indicato comprende i carichi permanenti e accidentali oltre al peso proprio del manufatto e dell'eventuale getto integrativo di 5 cm, espresso in kN/m<sup>2</sup>