

Dimensioni e pesi elemento						
H Trave (cm)	Travi Rettangolari		Travi a L		Travi a T	
	Tipo R 35	Tipo R 50	Tipo L 35	Tipo L 50	Tipo T 35	Tipo T 50
	Peso kg/m	Peso kg/m	Peso kg/m	Peso kg/m	Peso kg/m	Peso kg/m
60	525	750	675	900	825	1050
70	615	875	765	1025	915	1175
80	700	1000	850	1150	1000	1300
90	790	1125	940	1275	1090	1425
100	875	1250	1025	1400	1175	1550
110	965	1375	1115	1525	1165	1675
120	1050	1500	1200	1650	1350	1800

Tabella delle lunghezze indicative delle travi per tipologia di utilizzo (esprese in m)

H TRAVE (cm)	Copertura		Soppalco							
	R60	R120	R60				R120			
	Sov. 1,60 ÷ 2,20		Sov. 2,50	Sov. 5,00	Sov. 8,00	Sov. 10,00	Sov. 2,50	Sov. 5,00	Sov. 8,00	Sov. 10,00
	Nocciolo 35-50 cm		Nocciolo 35 cm				Nocciolo 50 cm			
60	4,0 ÷ 8,0	5,0 ÷ 7,0	4,0 ÷ 7,0	4,0 ÷ 7,0	4,0 ÷ 6,5	4,0 ÷ 6,0	4,0 ÷ 8,0	4,0 ÷ 8,0	4,0 ÷ 7,5	4,0 ÷ 7,0
70	5,0 ÷ 9,0	5,0 ÷ 8,0	5,0 ÷ 8,0	5,0 ÷ 8,0	5,0 ÷ 7,5	4,0 ÷ 7,0	5,0 ÷ 9,0	5,0 ÷ 8,5	5,0 ÷ 8,0	5,0 ÷ 7,5
80	6,0 ÷ 10,0	6,0 ÷ 9,0	6,0 ÷ 9,0	6,0 ÷ 8,5	6,0 ÷ 8,0	6,0 ÷ 7,5	6,0 ÷ 9,5	6,0 ÷ 9,0	6,0 ÷ 8,5	6,0 ÷ 8,0
90	7,0 ÷ 11,0	7,0 ÷ 10,0	7,0 ÷ 9,5	7,0 ÷ 9,0	7,0 ÷ 8,0	6,0 ÷ 7,5	7,0 ÷ 9,5	7,0 ÷ 9,0	7,0 ÷ 8,5	7,0 ÷ 8,0
100	7,0 ÷ 12,0	7,0 ÷ 11,0	7,0 ÷ 10,0	7,0 ÷ 9,0	7,0 ÷ 8,0	6,0 ÷ 7,5	7,0 ÷ 10,0	7,0 ÷ 9,0	7,0 ÷ 8,5	7,0 ÷ 8,0
110	8,0 ÷ 13,0	8,0 ÷ 12,0	8,0 ÷ 10,0	7,0 ÷ 8,5	7,0 ÷ 8,0	6,0 ÷ 7,5	8,0 ÷ 10,0	7,0 ÷ 9,0	7,0 ÷ 8,5	6,0 ÷ 8,0
120	9,0 ÷ 14,0	9,0 ÷ 13,0	8,0 ÷ 9,5	7,0 ÷ 8,5	7,0 ÷ 8,0	5,0 ÷ 6,5	8,0 ÷ 9,5	7,0 ÷ 8,5	7,0 ÷ 8,5	5,0 ÷ 7,0

Il sovraccarico indicato comprende i carichi permanenti e accidentali oltre al peso proprio del manufatto e dell'eventuale getto integrativo di 5 cm, espresso in kN/m².
Le travi con il nocciolo da 60 cm sono elementi speciali.